

Features

- Great cost-effective for front-lit display
- White opaque substrate for front-lit display
- Matte & Glossy surface available
- Best suited for Indoor or outdoor front-lit display under moderate weather conditions

Applications



Technical Data Sheet

Item Code	FBLFFX101099440	Test Method	
Base Fabric	1000D*1000D 9*9	DIN EN ISO2060	
Weight (GSM)	440	DIN EN ISO2286-2	
Tensile Strength	Warp (N/5cm)	1200	ISO527/3:1995
	Weft (N/5cm)	1200	ISO527/3:1995
Tear Strength	Warp (N/5cm)	230	ISO4674/1:2003
	Weft (N/5cm)	180	ISO4674/1:2003
Adhesion Strength	N/A	DIN53357:1982	
Temperature	-30°C/+70°C	ISO13934-1:1999	
RF Weldable (Heat Sealable)	YES	DIN53354	
Flame Retardant	B1/M1/M2/NFPA701		

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■

	<p>Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District, Haining, Zhejiang, China Tel: +86-573-80776996 Fax: +86-573-80776998 Mob/Skype/Wechat/WhatsApp: +86-15858322153 mailto:contact@hncomax.com https://www.hncomax.com</p>	
---	--	---